



IMA Power Supply Series

For industrial, medical and IT applications

The IMA Power Supplies are available with 400W, 600W and 1000W output power and with 12V, 24V, and 48V output voltages. Additionally, they are equipped with a 5V Auxiliary DC Output. They units are designed with 1U height and have one of the smallest footprints in his class, combined with high efficiency of up to 94 %.The IMA sereis fulfills all medical and industrial safety standarsd. Each unit is also in a coated version for harsh environments.

Wide AC and DC input range

Each variant of the power supplies can be used either with AC input voltages from 80V_{AC} to 275V_{AC} and DC input voltages from DC 120V_{DC} to 300V_{DC}.

Wide output voltage range

The main output voltage can be adjusted in a wide range of $\pm 20\%$.
The 5V Auxiliary DC Output supplies your controller board with up to 2A.

Many built-in features

The unit comes along with a lot of useful features like Power good signaling, Remote ON/OFF, OCP, OTP, OVP and Remote voltage drop compensation. The PMBus™ communication interface allows to control and program the unit.

Easy scalability

For higher power rates or for redundancy, up to 8 units can be used in parallel. Active Load sharing allows intelligent power adaption to your application.



Industrial



Medical



IT



IMA Power Supply Series

AC/DC Input	IMA-x400-xx			IMA-x600-xx			IMA-1000-xx		
	12V	24V	48V	12V	24V	48V	12V	24V	48V
Nominal AC input voltage range	100 V _{AC} to 240 V _{AC}								
AC operating input voltage range	80 V _{AC} to 275 V _{AC}								
Nominal input frequency	50/60 Hz								
Input frequency range	47 Hz to 63 Hz								
DC input voltage range	120 V _{DC} to 300 V _{DC}								
Maximum input current	6 A at 80 V _{AC} / 3.8 A at 120 V _{DC}			9 A at 80 V _{AC} / 5.7 A at 120 V _{DC}			15 A at 80 V _{AC} / 9.5 A at 120 V _{DC}		
Efficiency at full load at 230 V _{AC} ¹⁾	92 %	94 %	94 %	92 %	94 %	94 %	93 %	94 %	94 %
Power factor (cos φ)	0.9 (typical)								

Main DC Output

	12V _{DC}	24V _{DC}	48V _{DC}	12V _{DC}	24V _{DC}	48V _{DC}	12V _{DC}	24V _{DC}	48V _{DC}
Nominal DC output voltage	12 V _{DC}	24 V _{DC}	48 V _{DC}	12 V _{DC}	24 V _{DC}	48 V _{DC}	12 V _{DC}	24 V _{DC}	48 V _{DC}
Minimum DC output voltage	9.6 V _{DC}	19.2 V _{DC}	38.4 V _{DC}	9.6 V _{DC}	19.2 V _{DC}	38.4 V _{DC}	9.6 V _{DC}	19.2 V _{DC}	38.4 V _{DC}
Maximum DC output power	400 W			600 W			1000 W		
Total DC output voltage regulation	2.25 %								
Maximum DC output current	33.3 A	16.7 A	8.3 A	50 A	25 A	12.5 A	84 A	42 A	21 A

Auxiliary DC Output

Maximum output power	400 W			600 W			1000 W		
Nominal DC output voltage	5 V								
Maximum DC output current	0.5 A			0.5 A			2 A		
Total output voltage regulation	2.25 %								

Protection

DC output over voltage protection	Yes, latch mode, Main DC Output and Auxiliary DC Output								
DC output over current protection	Yes, auto recovery, Main DC Output and Auxiliary DC Output								
Short circuit protection	Yes, auto recovery, Main DC Output and Auxiliary DC Output								
Over temperature protection	Yes, auto recovery, Main DC Output and Auxiliary DC Output								

Mechanical design

Dimensions L x W x D	176.8 x 101.6 x 40.6 mm (6.96 x 4 x 1.6 in)	203.1 x 101.6 x 40.6 mm (8.0 x 4.0 x 1.6 in)	209.5 x 127 x 40 mm (8.035 x 5 x 1.57 in)
Weight	0.960 kg (2.12 lb)	1.1 kg (2.43 lb)	1.6 kg (3.53 lb)
Cooling system	System airflow cooling or natural convection cooling	Fan with variable speed control	2 fans with variable speed control

Connectors

AC/DC input terminal block	Block M3.5 x 3 pins
Main DC output terminal block	Block M5 x 2 pins ¹⁾
Auxiliary DC output + signals port	Connector x 14 pins

1) IMA-x600-24 and -48; M4 x 2 pins

Environmental conditions

Operating temperature range	-20 °C ... +70 °C (-4 °F to +158 °F)
Storage temperature range	-40 °C ... +85 °C (-40 °F to +185 °F)
Relative humidity	< 95 %, non-condensing
Maximum operating altitude	-200 m to 5000 m (-650 ft to 16400 ft)

Safety and EMC

Safety	IEC/EN 60950-1, Edition 2 and all national deviations
	IEC/EN 60601-1, Edition 3 (tested against Edition 2, too) and all national deviations
Protection class	I
EMC	see data sheet on www.DeltaPSU.com



ASIA

Delta Electronics, Inc.
3 Tungyuan Road, Chungli Industrial Zone,
Taoyuan County 32063, Taiwan, R.O.C
Tel: +886 3 452 6107
Fax: +886 3 434 3617

**Delta Electronics (Shanghai) Co., Ltd.
Headquarters**

No. 182 Minyu Road, Pudong,
Shanghai, P.R.C. 201209
Tel: +86 21 68723988
Fax: +86 21 68723996

**Delta Electronics (Shanghai) Co., Ltd.
Beijing Branch**

No. 7 Building, 6th Courtyard, Beichen East Rd.,
Chaoyang Dist., Beijing, P.R.C. 100105
Tel: +86 10 82253225
Fax: +86 10 82251360

Delta Electronics (Thailand) PCL.

909 Soi 9, Moo 4, Bangpoo Industrial Estate
(E.P.Z.), Pattana 1 Rd., T. Phrakasa, A. Muang,
Samutprakarn 10280, Thailand
Tel: +662 709 2800
Fax: +662 709 2827

Delta India Electronics Pvt. Ltd.

Plot No. 43, Sector - 35, HSIIDC,
Gurgaon, Haryana 122001
Tel: +91 124 4874900
+91 124 4169040
Fax: +91 124 4874945

Delta Electronics (Japan), Inc.

2-1-14 Shibadaimon, Minato-Ku,
Tokyo, 105-0012, Japan
Tel: +81 3 5733 1155
Fax: +81 3 5733 1255

Delta Electronics (Korea), Inc.

1511, Byucksan Digital Valley 6-Cha,
Gasam-dong, Geumcheon-gu,
Seoul, 153-704, Korea
Tel: +82 2 515 5303
+82 2 515 5305
Fax: +82 2 515 5302

NORTH AMERICA

**Delta Products Corporation
North American Headquarters**
46101 Fremont Blvd.
Fremont, CA 94538, U.S.A.
Tel: +1 510 668 5100

CENTRAL AND SOUTH AMERICA

Delta Greentech (Brasil) S.A.

Rua Itapeva, 26 - 3º, andar Edificio Itapeva,
One - Bela Vista 01332-000 - São Paulo - SP -
Brasil
Tel: +55 11 3568 3850
Fax: +55 11 3568 3865

**Delta Electronics International Mexico,
S.A. de C.V.**

Via Dr. Gustavo Baz No. 2160,
Fracc. Ind. La Loma, Tlalnepantla de Baz,
Estado de México, 54060, Mexico
Tel: +52 55 2628 3015

EUROPE

**Delta Electronics (Netherlands) B.V.
EMEA Headquarters**

Zandsteen 15
2132 MZ Hoofddorp, The Netherlands
Tel: +31 20 655 0975
Fax: +31 20 655 0999