

PRODUCT SELECTION GUIDE

| Industrial Power Supplies

New products are frequently introduced. Please visit www.DeltaPSU.com for latest product updates.

| Product Type | Series | Model Name | Output Voltage | Output Current | Input Current | Input Voltage Range |
|-------------------|---------|---------------|----------------|----------------|--|---------------------|
| Redundancy Module | CliQ II | DRR-20□ | 22-60V | 20.0A | (1+1 Redundancy) = Nominal 2 × 12.5A (N+1 Redundancy) = Nominal 2 × 10A | 22-60Vdc |
| | | DRR-40□ | | 40.0A | (1+1 Redundancy) = Nominal 2 × 25A (N+1 Redundancy) = Nominal 2 × 20A | |
| Buffer Module | CliQ II | DRB-24V020AB□ | 24V | 20.0A | Charging Mode: < 0.6A | 22.8-28.8Vdc |
| | | DRB-24V040ABN | | 40.0A | Charging Mode: < 0.6A | |
| DC-UPS Module | CliQ II | DRU-24V40ABN | 24V | 40.0A | Charging Mode: 2.0A ± 1.0A | 24-28Vdc |
| | Chrome | DRU-24V10ACZ | | 10.0A | Charging Mode: 0.5A ± 0.1A | |

Redundancy Module Model Numbering

| DR | R – | XX | □ |
|----------|---------------------------------------|--|---|
| DIN Rail | Product Type R - Redundancy Module | Output Current 20 - 20A 40 - 40A | A - Metal Case, with Class I, Div 2 N - Metal Case, without Class I, Div 2 |

DC-UPS Module and Buffer Module Model Numbering

| DR | □ – | 24V | XXXA | □ | □ |
|----------|--|----------------|----------------|---|---|
| DIN Rail | Product Type U - DC-UPS Module B - Buffer Module | Output Voltage | Output Current | B - CliQ II Series C - Chrome Series | A - Metal Case, with Class I, Div 2 N - Metal Case, without Class I, Div 2 Z - Plastic Case, without Class I, Div 2 |