

Issue Date: December 21, 2011

Introducing Panel Mount 24V 150W (High Line Version)

QUALITY

Highlights & Features

- Full corrosion resistant Aluminium casing
- Ease of wire connection to terminals
- Overload, over voltage, and over temperature protections
- Input voltage 180-264Vac @ 230Vac
- MTBF: > 700,000 hrs.

PRICE

For more information, visit www.DeltaPSU.com

Delta Electronics introduces a 24V 150W High Line PMC Panel Mount Power Supply operating only at High Line input voltage 180-264Vac @ 230Vac. Like its predecessors, the weight of the compact and unique aluminum body weight only 0.54Kg. The product is encased in a full corrosion resistant Aluminum casing. The efficiency of the 24V 150W PMC is >87% typ. and can sustain an industrial leading MTBF of more than 700,000 hours. The model also includes overvoltage, over temperature and overload protections.

This attractive price/performance ratio model is suitable for China, India, Australia, Finland, United Kingdom and other countries with high line input voltage source. For more information, please visit www.DeltaPSU.com or email vl@delta.co.th.

PMC-24V150W2AA SPECIFICATIONS

Input Voltage	180-264Vac (DC input 220-375Vdc)
Output Voltage	24V
Efficiency	> 87.0% @ 230Vac
Leakage Current	< 1mA @ 240Vac
Hold-up Time	> 20ms @ 230Vac with 150W load
MTBF	> 700,000 hrs.



- Apparatus constructions
- Automotive engineering
- Tool building
- Coffee machines
- General automation and machine applications

Upcoming Events

- **BOI Fair 2011**
Location: Bangkok, Thailand
Dates: 5 – 13 January 2012
- **Elecrama 2012**
Location: Mumbai, India
Dates: 18 – 22 January 2012
- **IMTEX 2012**
Location: Bangalore, India
Dates: 19 – 24 January 2012
- **Plast India 2012**
Location: New Delhi, India
Dates: 1 – 6 February 2012

FREE NAME CARD HOLDER

For our valued distributors.
While stocks last.

