

# DeltaPSU News

The World's No. 1 Provider of Switching Power Supplies



Issue Date: December 21, 2012

## CliQ<sup>II</sup>

### CliQ II 48V Series: Highlights & Features



- ▲ Designed for Class I, Div 2 Hazardous Locations and ATEX environments
- ▲ IP20 Certified
- ▲ Overvoltage / Overcurrent / Over Temperature Protections
- ▲ 150% Power Boost (steady state peak load) for 5 seconds
- ▲ MTBF: > 500,000 hours as per Telcordia

**AVAILABLE MODELS:** DRP048V060W1BA, DRP048V120W1BA, DRP048V240W1BA, DRP048V480W1BA

## DELTA LAUNCHES CliQ II 48V SERIES

Delta Electronics Group has announced the launch of CliQ II 48V 1 Phase DIN Rail Standard Power Supply Series. The series is available in power ratings of 60W, 120W, 240W and 480W. They are also compatible with Delta's CliQ II DRR-20A Redundancy Module to enable zero system down time for the customer when one of the power supply fails or is being disconnected unexpectedly.

The CliQ II 48V 1 Phase DIN Rail Standard Power Supply Series has 150% Power Boost for 5 seconds and efficiency of more than 90%. The 48V specification is commonly applied in the telecom industry. Therefore, such Power Boost feature can help to prevent system from shutting down during sudden output surge. The products fulfill protection class IP20, and complies with UL60905-1, UL508, CSA C22.2 No.107.1-01, SIQ mark according to EN60950-1 and EN55011 for industrial applications. The CliQ II 48V 1 Phase series is ATEX ready with Conformal coating on the PCBAs which prevents components damage in highly polluted environment.

**CliQ II 48V SERIES ARE NOW AVAILABLE FOR SHIPMENT.**

For more information and enquiries, please visit Delta standard power supplies homepage at [www.DeltaPSU.com](http://www.DeltaPSU.com).

### Upcoming Events

- **CBM Day**  
Location: Bangkok, Thailand  
Dates: 16 – 17 January 2013
- **AHR Expo**  
Location: Dallas, Texas, U.S.A.  
Dates: 28 – 30 January 2013

### PMT PANEL MOUNT POWER SUPPLY



■ 24V 350W  
**PMT-24V350W1AG**  
(With UL mark only)

\*Available for shipment

