

Issue Date: May 6, 2014

Delta Introduces CliQ II DC-UPS Module with Battery Management



DRU-24V40ABN
24V 40A / DC-UPS MODULE

CliQ II

▲ SAFETY APPROVALS



▲ TYPICAL APPLICATIONS



Delta Electronics introduces CliQ II DC-UPS module to support 24V system with up to 40A output and back up time of 4.5 minutes for 15AH battery capacity. DRU-24V40ABN offers a wide input voltage from 24-28V and a wide operating temperature range from -20°C to +60°C. This product comes with potential free contacts for battery management signals and LED indicator for battery status.

Highlights & Features

- Full corrosion resistant Aluminium chassis
- Suitable for 24V system up to 40A
- Built-in relay contacts for DC OK, Discharge and Battery Fail
- LED indicator for DC OK, battery fail, battery reverse polarity and battery discharge
- Wide operating temperature range from -20°C to +60°C
- Conformal coating option on PCBA to protect against chemical and dust pollutants

Other product details for DRU-24V40ABN are available on the homepage.

AVAILABLE FOR SHIPMENT NOW

New models are introduced on a regular basis. For more information or enquiries, please do not hesitate to contact your local Delta Electronics distributor or visit www.DeltaPSU.com.

Upcoming Events

- **SPS IPC Drives Italia**
Location: Parma, Italy
Dates: 20 – 22 May 2014
- **Techno-Frontier**
Location: Tokyo, Japan
Dates: 23 – 25 July 2014
- **AMTEX**
Location: New Delhi, India
Dates: 25 – 28 July 2014

CHROME DIN RAIL POWER SUPPLY



- **DRC-24V30W1AZ (24V 30W)**
AVAILABLE FOR SHIPMENT NOW